

Englewood

Code Enforcement

P.O. Box 228 • Englewood, N.J. 07631 • www.cityofenglewood.org

Receipt No.	CCO Inspector
CCO No	Date Inspected
Cash or Check #	Date Received
Fee \$	
	ATE OF CONTINUED OCCUPANCY
FOR THE RESALE OF A C	CONDO, 1 & 2 FAMILY - \$150 * 3 & 4 FAMILY - \$250
Seller-Name	Tel:
Seller-Email Address	
Property Address	
Block Lot	Use Group
No. of Bedrooms N	No. of BathroomsNo. of Kitchens
Buyer-Name	
Buyer-Present Address	
	Tel:
No. of People <u>Presently</u> Residing At Pr	remises Before Sale
No. of People Who Will Occupy Premi	ises After Sale
	m. 1
	Tel:
Email Address	
	Tel:
Email Address	
I hereby certify that I have read this Chapter 159 of the city codes of the C	application thoroughly and agree to conform to the provisions city of Englewood.
PRINT NAME CLEARLY	SELLER/AGENT/ATTORNEY SIGNATURE

TO RECEIVE A CCO THE ITEMS LISTED BELOW MUST BE COMPLIANT WITH APPLICABLE STATE LAW AND LOCAL ORDINANCE

- 1. House No. in contrasting colors (3) inches high must be permanently affixed in the vicinity of the front door
- 2. Carbon monoxide alarms must be installed outside of any sleeping area within (10) feet of bedroom
- 3. No dead bolt inside with key
- 4. All egress doors shall be readily operable from the inside without the use of a key or special knowledge or effort
- 5. All egress windows in bedroom should must open easily
- 6. No broken glass
- 7. Working fans must be installed in bathroom without windows
- 8. Handrails must be installed for (4) or more steps
- 9. Water heater pipe within 6" of floor
- 10. Flue on heater no leaks around vent pipe
- 11. No holes in garage ceiling
- 12. At least (1) portable fire extinguisher must be mounted and installed. (See below)
 - Fire extinguisher shall be listed, labeled, charged and operable.
 - The size shall be no smaller than 2A: 10B: c rated for residential use and weighs no more than 10lbs.
 - The hangers and brackets supplied by the manufacturer must be used.
 - The top of the extinguisher must not be more than (5) feet above the floor.
 - The extinguisher must be near a room exit or travel path that provides an escape route to the exterior kitchen

Smoke detectors must be installed in accordance with NFPA Standard 74-1984 as follows:

- 1. (1) on each level of the premises including basements and walk up attics
- 2. (1) outside of any sleeping area within (10) feet of bedroom
- 3. If the smoke detectors are interconnected, have password to turn off & reset system
- 4. Smoke detectors may be battery powered and will be listed in accordance with ANSI/UL 217
- 5. A/C powered smoke detectors are permitted

*ALL OPEN PERMITS <u>MUST</u> HAVE FINAL INSPECTIONS BEFORE CCO APPLICATIONS ARE ACCEPTED

*APPLICATIONS SHOULD BE SUBMITTED AT LEASE (10) DAYS BEFORE THE CLOSING DATE

*CCO INSPECTIONS WILL BE SCHEDULED <u>5-7 BUSINESS DAYS</u> FROM THE DATE THE APPLICATION IS SUBMITTED

* <u>BANK OWNED PROPERTIES</u> - SUBMIT A COPY OF THE CONTRACT OF SALE OR A NOTARIZED LETTER FROM THE BANK ON THEIR COMPANY LETTERHEAD STATING THAT THEY ARE THE OWNERS AND THE PROPERTY IS BEING SOLD TO THE NEW BUYER

*IF THE BUYER CHANGES (30) DAYS AFTER THE APPLICATION WAS SUBMITTED, A NEW CCO APPLICATION & PAYMENT MUST BE SUBMITTED

IF YOU HAVE ANY QUESTIONS PLEASE CONTACT THE INSPECTOR JAHVIA GRIFFIN AT (201) 510-8201